

DECLARATION OF PERFORMANCE According to Regulation (UE) 305/2011	
5.Where applicable, name and address of the agent (art. 12-2) 6.Assessment and verification system for constancy of performance (annex 5)	: e : System 3
7.Notified Laboratory	: KIWA CERMET ITALIA SpA (NB 0476)
Test report number (based on System 3)	4003081/C-444
8. Declared performance	
Harmonized technical specification	EN 14785:2006
Essential characteristics	Performance
Reaction to fire	A1
Distance to combustible materials	Minimum distance in mm :
	Rear = 500mm
	Side = 500mm
	Front = 1000mm
Dials of humaing fuel felling out	Floor =
Risk of burning fuel falling out	Pass
Emission of combustion products (mg/Nm ³ -13% de O ₂)	CO 66
Nominal heat output	NOx 98,7 OGC 4,2
	PM 8,3
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum operating pressure	NPD
Mechanica resistance (to carry a chimney flue)	NPD
Thermal output	1110
Nominal heat output	8,07kW
Reduced nominal heat output	3,45kW
Efficiency	,
Nominal heat output	90,72%
Reduced heat output	94,57%
Flue gas temperature	
Nominal heat output	119,1°C
Reduced heat output	66,7°C

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer in point 4.

San Vendemiano, 21-12-2018

Signed for and on behalf of the manufacturer:

Andrea Da Ros

Technical Manager

Reg. Imp. TV - C.F. / P.IVA 03892500269 Capitale Sociale € 100.000,00 i.v. Tel. +39 0438 62717 Fax +39 0438 453799