

DECLARATION OF PERFORMANCE According to Regulation (UE) 305/2011	
<ol> <li>Unique identification code of the product type</li> <li>Model and/or batch and/or serial number (art.11-4)</li> <li>Intended uses of the product in accordance with the applicable harmonized technical specification, as foreseen by the manufacture (art. 11-5)</li> </ol>	rer (wood pellets) without hot water production
5.Where applicable, name and address of the agent (art. 12-2) 6.Assessment and verification system for constancy of performan (annex 5)	: ice : System 3
7.Notified Laboratory	: KIWA CERMET ITALIA SpA (NB 0476)
Test report number (based on System 3)	2003081/C-427
8. Declared performance	
Harmonized technical specification	EN 14785:2006
Essential characteristics	Performance
Reaction to fire	A1
Distance to combustible materials	Minimum distance in mm :
	Rear = 500mm
	Side = 500mm
	Front = 1000mm
	Floor =
Risk of burning fuel falling out	Pass
Emission of combustion products (mg/Nm <sup>3</sup> -13% de O <sub>2</sub> )	CO 108
Nominal heat output	NOx 113,4
	OGC 5
	PM 16,8
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum operating pressure	NPD NPD
Mechanica resistance (to carry a chimney flue)	NPD
Thermal output	11 07104
Nominal heat output Reduced nominal heat output	11,97kW 4,98kW
Efficiency	4,300.00
•	90,87%
Nominal heat output Reduced heat output	90,87% 93,83%
Flue gas temperature	33,0370
Nominal heat output	107.9°C
Reduced heat output	73,9°C

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer in point 4.

San Vendemiano, 25-10-2018

Signed for and on behalf of the manufacturer:

Andrea Da Ros

Technical Manager

Reg. Imp. TV - C.F. / P.IVA 03892500269 Capitale Sociale € 100.000,00 i.v. Tel. +39 0438 62717 Fax +39 0438 453799